

MIGHTY-RITE[®]

SPLIT-GROUNDING BUSHINGS



THE RITE CHOICE FOR ANY JOB.

 **BRIDGEPORT**
www.bptfittings.com



SCAN TO
SEE THE
MIGHTY-RITE
IN ACTION

MIGHTY-RITE® SPLIT-GROUNDING BUSHINGS

THE RIGHT SOLUTION BEFORE OR AFTER YOU PULL WIRE

Install MIGHTY-RITE Split Grounding Bushings before or after you pull wire and make connections. Its hinged design and adjustable grounding lug deliver installation flexibility on every job. So you can move on to the next job faster. It's another contractor innovation from Bridgeport.



- CAN BE INSTALLED BEFORE WIRE PULL, OR AFTER – WITHOUT EXPENSIVE REWORK
- ADJUSTABLE GROUNDING LUG ACCEPTS WIRE EASIER
- PULLING LARGER CONDUCTOR WIRE IS EASIER WHEN YOU CAN INSTALL GROUNDING BUSHINGS AFTER THE PULL
- LOW PROFILE
- HINGED DESIGN ADJUSTS AND ALIGNS EASIER – EVEN IN TIGHT SPOTS
- cULus LISTED
- AVAILABLE IN 3/4 TO 4-INCH TRADE SIZES
- 150°C CAPTIVE NYLON INSULATOR



FOR MORE INFORMATION, VISIT: WWW.BPTFITTINGS.COM

BUSHINGS ENGINEERED WITH THE BRIDGEPORT DIFFERENCE



Bridgeport bushings are born from the minds of contractors. You spoke; we listened and designed.


From our insulated grounding bushings to our patented and problem-solving Mighty-Rite® Split Grounding Bushings, you now get the quality, performance and innovation you needed and expected.

Expect more. Get a Bridgeport Bushing.



Mighty-Rite® Split Grounding Bushings

Mighty-Rite's hinged design and adjustable grounding lug deliver installation flexibility on every job. Aluminum alloy lug. Patented.

 File No. E20412

Zinc Die Cast / Nylon Insulator - 150°C

Catalog Number	Grounding Lug Wire Capacity		Trade Size	Unit Qty.	Std. Qty.
	Min. Solid Strand	Max. Solid Strand			
SGB-382CL	#14 to #4		3/4"	25	250
SGB-383CL	#14 to #4		1"	25	250
SGB-38414	#14 to #4		1 1/4"	20	200
SGB-384CL	#14 to #1/0		1 1/4"	20	200
SGB-38514	#14 to #4		1 1/2"	20	200
SGB-385CL	#14 to #1/0		1 1/2"	20	200
SGB-38614	#14 to #4		2"	10	100
SGB-386CL	#14 to #1/0		2"	10	100
SGB-38740	#6 to 250 MCM		2 1/2"	---	25
SGB-387CL	#14 to #1/0		2 1/2"	---	25
SGB-38840	#6 to 250 MCM		3"	---	25
SGB-388CL	#14 to #1/0		3"	---	25
SGB-38940	#6 to 250 MCM		3 1/2"	---	25
SGB-389CL	#6 - #3/0		3 1/2"	---	25
SGB-39040	#6 to 250 MCM		4"	---	20
SGB-390CL	#6 to #3/0		4"	---	20



Insulated Grounding Bushings

Used with locknut to terminate service conduit to cabinet. Aluminum alloy lug provided for bonding jumper to neutral busbar. Plastic liner prevents damage to wire insulation.

 File No. E20412

Malleable Iron / Nylon Insulator - 150°C

Catalog Number	Grounding Lug Wire Capacity		Trade Size	Unit Qty.	Std. Qty.
	Min. Solid Strand	Max. Solid Strand			
381	#14 to #4		1/2"	50	500
382	#14 to #4		3/4"	50	500
383	#14 to #4		1"	25	250
384	#14 to #1/0		1 1/4"	20	200
384-14	#14 to #4		1 1/4"	20	200
385	#14 to #1/0		1 1/2"	20	200
385-14	#14 to #4		1 1/2"	20	200
386	#14 to #1/0		2"	10	100
386-14	#14 to #4		2"	10	100
387	#14 to #1/0		2 1/2"	---	25
387-40	#6 to 250 MCM		2 1/2"	---	25
388	#14 to #1/0		3"	---	25
388-40	#6 to 250 MCM		3"	---	25
389	#14 to #1/0		3 1/2"	---	25
389-40	#6 to 250 MCM		3 1/2"	---	25
390	#14 to #1/0		4"	---	20
390-40	#6 to 250 MCM		4"	---	20
391	#6 to 250 MCM		5"	---	5
392	#6 to 250 MCM		6"	---	5

Zinc Die Cast / Nylon Insulator - 150°C

Catalog Number	Grounding Lug Wire Capacity		Trade Size	Unit Qty.	Std. Qty.
	Min. Solid Strand	Max. Solid Strand			
381-DC	#14 to #4		1/2"	50	500
382-DC	#14 to #4		3/4"	50	500
383-DC	#14 to #4		1"	25	250
384-DC	#14 to #1/0		1 1/4"	20	200
384-DC14	#14 to #4		1 1/4"	20	200
385-DC	#14 to #1/0		1 1/2"	20	200
385-DC14	#14 to #4		1 1/2"	20	200
386-DC	#14 to #1/0		2"	10	100
386-DC14	#14 to #4		2"	10	100
387-DC	#14 to #1/0		2 1/2"	---	25
387-DC40	#6 to 250 MCM		2 1/2"	---	25
388-DC	#14 to #1/0		3"	---	25
388-DC40	#6 to 250 MCM		3"	---	25
389-DC	#14 to #1/0		3 1/2"	---	25
389-DC40	#6 to 250 MCM		3 1/2"	---	25
390-DC	#14 to #1/0		4"	---	20
390-DC40	#6 to 250 MCM		4"	---	20



Bushings

Used with locknut to protect conductors inside threaded rigid or IMC conduit entering a box. Rounded surface of bushing prevents damage to wire insulation.

File No. E9391: 321 thru 332

File No. E11259: 321-B thru 330-B

File No. LR39354

Polypropylene - 105°C

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
321	1/2"	100	1000
322	3/4"	100	1000
323	1"	50	500
324	1 1/4"	---	100
325	1 1/2"	---	100
326	2"	---	50
327	2 1/2"	---	25
328	3"	---	25
329	3 1/2"	---	25
330	4"	---	20
331	5"	---	5
332	6"	---	5



Nylon - 150°C

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
321-B	1/2"	100	1000
322-B	3/4"	100	1000
323-B	1"	50	500
324-B	1 1/4"	---	100
325-B	1 1/2"	---	100
326-B	2"	---	50
327-B	2 1/2"	---	25
328-B	3"	---	25
329-B	3 1/2"	---	25
330-B	4"	---	20



Insulated Bushings

Used with locknut to protect conductors inside threaded rigid or IMC conduit entering a box. Plastic liner prevents damage to wire insulation. All products rated 150°C except catalog numbers 371 and 372 which are rated 105°C.

File No. E9391

Malleable Iron / Nylon Insulator

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
361	1/2"	100	1000
362	3/4"	100	1000
363	1"	50	500
364	1 1/4"	10	100
365	1 1/2"	10	100
366	2"	10	100
367	2 1/2"	2	10
368	3"	2	10
369	3 1/2"	---	5
370	4"	---	5
371	5"	---	5
372	6"	---	5

Zinc Die Cast / Nylon Insulator

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
361-DC	1/2"	100	1000
362-DC	3/4"	100	1000
363-DC	1"	50	500
364-DC	1 1/4"	10	100
365-DC	1 1/2"	10	100
366-DC	2"	10	100
367-DC	2 1/2"	2	10
368-DC	3"	2	10
369-DC	3 1/2"	---	5
370-DC	4"	---	5



Pull Caps

Used for capping EMT, rigid and most bushings.

Polyethylene

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
341	1/2"	100	1000
342	3/4"	100	1000
343	1"	100	1000
344	1 1/4"	50	250
345	1 1/2"	25	100
346	2"	25	100



Bushing Pennies

Used inside bushing to prevent foreign matter from entering conduit.


Galvanized Steel


Catalog Number	Trade Size	Unit Qty.	Std. Qty.
1661	1/2"	500	1000
1662	3/4"	250	500
1663	1"	100	200
1664	1 1/4"	50	100
1665	1 1/2"	50	100
1666	2"	50	100
1667	2 1/2"	50	100
1668	3"	50	100
1669	3 1/2"	25	100
1670	4"	25	100
1671	5"	25	100



Knockout Insulating Bushings

Converts metallic box rough edged holes to smooth insulated holes for protection of electrical, voice, data and video cables.

 File No. LR24719

 File No. E240912 (9791 thru 9796)

Nylon - 105°C

Catalog Number	K.O.	K.O. Dia.	Unit Qty.	Std. Qty.
9791	1/2"	.875"	100	1000
9792	3/4"	1.109"	100	1000
9793	1"	1.375"	50	500
9794	1 1/4"	1.734"	50	500
9795	1 1/2"	1.984"	25	250
9796	2"	2.469"	20	100
9797	2 1/2"	2.969"	20	100




Stud Bushings

Protects wire insulation from abrasion in metal studs. Bushing allows smooth wire pulling. Used for all pre-punched shaped holes.

 File No. E11259

Polypropylene

Catalog Number	Hole Dia.	Unit Qty.	Std. Qty.
9882	---	50	500



Insulating Bushing

EMT bushing insulates telephone, computer, video and other low voltage wiring from sharp edges of EMT. Complies with NEC Article 300-15(c).

Polyethylene - 90°C

Catalog Number	Trade Size	Unit Qty.	Std. Qty.
TWB-51	1/2"	100	1000
TWB-52	3/4"	50	500
TWB-53	1"	25	250
TWB-54	1 1/4"	25	250
TWB-55	1 1/2"	---	100
TWB-56	2"	---	50
TWB-57	2 1/2"	---	25
TWB-58	3"	---	25
TWB-59	3 1/2"	---	25
TWB-60	4"	---	25

OTHER INNOVATIONS FROM BRIDGEPORT



- ▶ **Mighty-Bond® Enclosure Grounding Connectors**
Low cost and easy to use connector for securing grounding conductors at the enclosure. MC Series. Patent Pending.

- ▶ **Mighty-Bond® Enclosure Grounding Couplings**
Low cost and easy to use coupling for use with rigid conduit and for securing grounding conductors at the enclosure. MCC Series. Patent Pending.



- ▶ **Mighty-Bond® Raintight Grounding and Bonding Hubs**
Provide a listed method of bonding between ground electrode conductors (GEC), grounded conductors, bonding jumpers, and boxes, devices or enclosures. MCH Series. Patent Pending.

- ▶ **Mighty-Bond® Intersystem Bonding Bridge with Enclosure Grounding Coupling Kit**


Intersystem Bonding Bridge with Enclosure Grounding Coupling is used for securing and bonding ground electrode conductors to the enclosure. MBG Series. Patented.



THE BRIDGEPORT FITTINGS DIFFERENCE



Distributed by:



Bridgeport Fittings, Inc.
705 Lordship Blvd.
Stratford, CT 06615-7313

Voice: 203.377.5944
Fax: 203.381.3488
E-mail: sales@bptfittings.com

www.bptfittings.com



Printed in the U.S.A.
© 2012 Bridgeport Fittings, Inc. All rights reserved.

